



Safe Products | Sound Advice | Delivered  
800-451-3077 | RitzSafety.com

# SharpsMaster II® Wrinkle Rubber Dipped



EN 388



4X44F

## Specifications

Manufacturer P/N	9014
ANSI Cut Level	A9
EN Cut Level	4X44F
Dip Type	Palm Dipped
Shell Material	Cotton Blend
Interior Layer	SuperFabric® Material
Cuff Style	Elastic Cuff
Coating	Wrinkle Rubber
UOM	Pair

ITEM #	SIZES	COLOR
HEX9014	SM-LG	ORANGE/WHITE
HEX9014XL	XL	ORANGE/WHITE

## Product Description

HexArmor® sets the industry standard for needle protection with solutions for a variety of applications. Our needlestick-resistant products do more than pass industry-accepted testing methods; we put them through real-world applications countless times, with a history of undeniable success. The accepted standards of testing do not account for the many variables employees face on the jobsite, so HexArmor created their own tests, mirroring the conditions and hazards that our users face.

## Features

- Highest needlestick resistance available provided by the layering of SuperFabric® brand material
- Tested using actual 25 gauge needles against ANSI/ISEA 105 standard
- Highest level of cut resistance on noted enhanced areas, ANSI/ISEA Cut Level A9 and Needlestick Level 5
- Single-glove needle solution with incredible dexterity and comfort
- Wrinkle rubber palm coating with Actifresh™ anti-microbial treatment

## Application's / Industry

- Sheet Metal
- Waste Management
- Parts Handling
- Recycling
- Medical
- Biohazard

**For more information, CONTACT US: (800) 451-3077 | Sales@RitzSafety.com | RitzSafety.com**

Neither this document nor any other statement made herein by or on behalf of Ritz Safety should be construed as a warranty of merchantability or that any product promoted by Ritz Safety is fit for a particular purpose. User shall be exclusively responsible to assess the suitability of the product as specified for any individual application or use. Product features, design and protections zones and/or capabilities are subject to change. All gloves advertised as cut or puncture resistant are NOT CUT OR PUNCTURE PROOF. Do not use with moving or serrated blades or tools.