



Safe Products | Sound Advice | Delivered
800-451-3077 | RitzSafety.com

Ztek® Safety Eyewear



Product Description

The Pyramex Ztek® is a comfortable and economical safety glass that features ANSI Z87.1+ certified polycarbonate lenses and soft non-slip rubber temple tips to help prevent the sliding down of your glasses. The Ztek® is available in a wide variety of lens color options.

Features

- Integrated nose piece
- Soft, non-slip rubber temple tips provide non-binding fit
- Economical wrap-around single lens provides full panoramic view
- Scratch resistant polycarbonate lens provides 99% UVA/B/C protection

Manufacturer Specifications

ANSI Rating	Z87.1+ High Impact
UOM	Each
Quantity per box	12

Lens Specifications

Item #	Mfg. Item #:	Lens Color	Frame Color	Anti-Fog	Polarized	Dielectric
PYRS2510S	S2510S	Clear	Clear	No	No	No
PYRS2510ST	S2510ST	Anti-Fog Clear	Clear	Yes	No	No
PYRS2520S	S2520S	Smoke	Smoke	No	No	No
PYRS2520ST	S2520ST	Anti-Fog Smoke	Smoke	Yes	No	No
PYRS2530S	S2530S	Amber	Amber	No	No	No
PYRS2560S	S2560S	Infinity Blue	Blue	No	No	No
PYRS2575S	S2575S	Blue Mirror	Blue	No	No	No
PYRS2580S	S2580S	Indoor/Outdoor Mirror	Clear	No	No	No

For more information, CONTACT US: (800) 451-3077 | Sales@RitzSafety.com | RitzSafety.com

User shall be exclusively responsible to assess the suitability of the product as specified for any individual application or use. Product features, design and protection zones and/or capabilities are subject to change. These hearing protectors help reduce exposure to hazardous noise and other loud sounds. Misuse or failure to wear hearing protectors at all times that you are exposed to noise may result in hearing loss or injury. For proper use, see supervisor, User Instructions, or call Ritz Safety at 1-800-451-3077. If there is any drainage from your ear or you have an ear infection, consult with your physician before wearing earplugs. Failure to do so may result in hearing loss or injury. NRR Footnote: Research suggests that many users will receive less noise reduction than indicated by the NRR due to variation in earplug fit and wearing time. It is recommended that the NRR be reduced by 50% for estimating the average amount of noise reduction provided