

Clear Lens and Frame Glass

RTZ10S

BullShark Clear Lens and Frame Glasses offer unobstructed vision and reliable eye protection in various work environments. Designed with a clear, durable lens and a matching frame, these glasses provide excellent visibility while safeguarding against dust, debris, and other potential hazards. Ideal for indoor use or low-light conditions, these glasses combine comfort with functionality, making them a perfect choice for safety in industries like construction, manufacturing, and laboratory work.



MEETS ANSI/ISEA Z87.1-2020 Standards



PRESSURE

TAPERED LENS ELIMINATES DISTORTION



UVA/UVB/UVC

FEATURES

- Spatula Temple Design
- Scratch resistant
- · Frosted Clear Frame
- Integrated Nose Piece
- Provide 99.9% UV Protection
- Single-mold lens with 10 base curves
- Wrap style for maximum protection and clarity
- 180-degree acuity
- Meets ANSI/ISEA Z87.1-2020 standards

SPECS

Lens	Clear Uncoated
Light Transmittance	89%
Frame width	135mm
Frame Color	Frosted Clear
Temple Length	120mm
Weight	24grams



TORRENT

BULLHEAD SAFETY® EYE PROTECTION

BH111-UC



LENS Clear Uncoated

FRAME Frosted Clear

DESCRIPTION

The Torrent[™] is a traditionally styled safety glass with a 10 base curve single mold lens. The wrap style affords maximum protection and full 180-degree peripheral acuity.

FEATURES

- Single-mold lens with 10 base curve
- Wrap style for maximum protection and clarity
- 180-degree acuity
- Meets ANSI/ISEA Z87.1-2020 standards

TECHNOLOGY

All Bullhead Safety® Eyewear is made from 100% virgin materials. This style features lenses and frames constructed with the highest quality polycarbonate.



MEETS ANSI/IS Z87.1-2020 STANDARDS



RELIEVES E
PRESSURE [



TAPERED LENS ELIMINATES DISTORTION



UVA/UVB/UVC LIGHT RAYS

SPECIFICATIONS

LENS	LIGHT TRANSMITTANCE	FRAME TYPE	FRAME COLOR	WEIGHT	BASE CURVE	FRAME WIDTH	TEMPLE LENGTH	END OF TIPS WIDTH
Clear Uncoated	89%	Frameless	Frosted Clear	24 Grams	10	135 mm	120 mm	90 mm

PACKAGING

	EACH	INNER PACK	CASE
QUANTITY	1	12/box	12 boxes/case
UPC/GTIN	816368024240	10816368024247	20816368024244



