

RTZ3DHF

HI-VIZ CONSTRUCTION HARNESS W/ 3 D-RINGS

The Ritz Fall Protection Hi-Viz Construction harness with 3 D-rings is designed to provide fall protection and visibility for workers in high-risk construction environments. It has three D-rings located on the back and sides of the harness. The harness is made from durable materials that can withstand harsh job site conditions.



FEATURES

- Bright yellow-green color with reflective strips for enhanced visibility in low-light conditions.
- Features 3 D-rings located on the back and sides of the harness for increased versatility in positioning of the safety lanyard
- 5 Adjustment Points:
 - Torso Adjusters
 - Mating Chest Buckle
 - Tongue Buckle Legs
- Replaceable shoulder pads
- Shoulder and back padding (6" floating back belt)
- Lanyard parking loops located on the chest
- Made from durable materials that can withstand harsh job site conditions
- Adjustable to fit a range of body sizes
- Compliant with relevant safety standards

TECH SPECS

Item Type	Harness
ANSI User Capacity	130-310 lbs
OSHA User Capacity	130-420 lbs
Webbing Type & Material	100% Polyester
Webbing Strength	≥5000 lbs
D-Ring Type & Material	N-416L-R; Steel
D-Ring Strength	5000 lbs
Chest Buckle Type, Material & Strength	N-421+N-448; Steel; 3600 lbs
Waist Buckle Type, Material & Strength	N-422; Steel; 3600 lbs
Leg Buckle Type, Material & Strength	N-439X; Steel; 4000 lbs
Min. Breaking Strength & Max. Arrest Force	3600 lbs
ANSI Compliance Details	ANSI Z359.11-2021
Sizes	SM - MD • LG - XL

ANSI Standard Detail

ANSI Z359.11-2021