

RTZNC28R

8' DUAL SRL CABLE WITH REBAR HOOKS - CLASS 2

Ritz Fall Protection introduces NINJA™ Leading Edge SRL series, designed for superior fall protection in Class-2 applications. Engineered with a durable lifeline and integrated energy absorber, it provides enhanced safety by reducing fall forces while ensuring reliable performance in demanding work environments.



FEATURES

- **Integrated Energy Absorber** – Reduces fall forces by absorbing energy upon impact, enhancing user safety.
- **Lightweight Construction** – Designed for ease of use and reduced fatigue, allowing workers to move comfortably.
- **Lifeline Stop Mechanism** – Prevents excessive retraction, ensuring controlled movement and added security.
- **Enhanced Mobility** – Provides unrestricted movement, improving efficiency and comfort during work.
- **Dual SRL** – A twin-leg self-retracting lifeline system that allows continuous tie-off, enabling workers to move safely between anchor points without disconnecting, ensuring maximum fall protection and mobility.
- **Rubber Handle** – Offers a firm, non-slip grip for enhanced control and ease of handling.



TECH SPECS

Cable Material	3/16" Galvanized Steel
Cable Length	8 ft
Lifeline Connector	Dual Steel Rebar Hooks
Anchorage Connector	Forged Aluminum Swivel Anchorage Eye
Min. Breaking Strength	3600 lbs.
Max Arrest Distance	42"
Maximum Arrest Force	1800 lbs.
Average Arrest Force	1350 lbs.
ANSI User Capacity	130 lbs - 310 lbs / OSHA 420lbs
ANSI SRL Class	CLASS 2
Casing Material	Nylon

STANDARDS

Meets or exceeds the applicable industry standards, such as ANSI/ASSP Z359.14-2021 and OSHA requirements, ensuring its quality and performance in fall protection applications.