Ritz Safety®

Safe Products | Sound Advice | Delivered

800-451-3077 | RitzSafety.com

Ritz Radical Safety Eyewear

Product Description

The Ritz Radical safety glasses are designed to protect your eyes from dirt and debris while providing a cool, modern look. They feature a scratch-resistant, polycarbonate lens with a bayonet temple design and shiny, black nylon frames. Ritz Radical safety glasses are equipped with comfortable thermoplastic rubber clam shell nose piece and temples. These safety glasses provide 99.9% UV protection.

Features

- Scratch-Resistant Polycarbonate, Dual Wrap-Around Lens
- Shiny Black Nylon Frame
- Bayonet Temple Design
- Thermoplastic Nose Piece & Temples
- Provides 99.9% UV Protection

Manufacturer Specifications

ANSI Rating	Z87.1+ High Impact
UOM	Each
Quantity per box	12

Lens Specifications

Item #	Mfg. Item #:	Lens Color	Frame Color	Anti-Fog	Polarized	Dielectric
RTZRAD10S	EOB10S	Clear	Black	No	No	No
RTZRAD20S	EOB20S	Smoke	Black	No	No	No
RTZRAD50S	EOB50S	In/Outdoor	Black	No	No	No
RTZRAD70S	EOB70S	Silver Mirror	Black	No	No	No

For more information, *CONTACT US:* **(800) 451-3077 | Sales@RitzSafety.com | RitzSafety.com**

User shall be exclusively responsible to assess the suitability of the product as specified for any individual application or use. Product features, design and protection zones and/or capabilities are subject to change. These hearing protectors help reduce exposure to hazardous noise and other loud sounds. Misuse or failure to wear hearing protectors at all times that you are exposed to noise may result in hearing loss or injury. For proper use, see supervisor, User Instructions, or call Ritz Safety at 1-800-451-3077. If there is any drainage from your ear or you have an ear infection, consult with your physician before wearing earplugs. Failure to do so may result in hearing loss or injury. NRR Footnote: Research suggests that many users will receive less noise reduction than indicated by the NRR due to variation in earplug fit and wearing time. It is recommended that the NRR be reduced by 50% for estimating the average amount of noise reduction provided